



Windowcrafters

2033 Tucker Industrial Road, Tucker, GA 770-723-9900 www.windowcraftersinc.com

Vinyl Window SPECIFICATION 700 Series

Double Hung 700 – Double Glazed

Material	u PVC Vinyl
Color	Cream White or Tan , custom colors available
Operating Sashes	Top & Bottom
Tilt-in Feature	Top & Bottom
Frame Thickness	3 1/4"
Application	Replacement box unit – R, NC
Styles	DH, 2 lite slider, 3 lite slider, picture window, deadlite
Construction	Fusion welded frame and sashes for durable strength Exterior frame is beveled; window unit is fully wrapped in foam for added insulation
Glass	Cardinal 270® standard, Cardinal 366® upgrade
Spacer	Dura Platform® warm edge spacers in a 3/4" dual pane insulated glass, Argon optional
Balance System	Four Jaks® constant force standard
Weather-stripping	Duel “center fin” nylon felt
Sash Locks	Integral Interlocks, double locks on units 28” or wider
Vent Locks	DH, so sash can be open 3” yet still secure
Screen	Aluminum Frame / nylon mesh - full or half height

<u>PERFORMANCE:</u>	<u>DH 270 LE*</u>	<u>DH 366LE**</u>
<u>Duraseal/Argon</u>	U Factor = 0 .29	U Factor = 0.29
(no grids / grids)	SHGC = 0.28/0.26	SHGC = 0.21/0.19
<u>Duralite/Argon</u>	U Factor = 0.28	U Factor = 0.27
(no grids / grids)	SHGC = 0.28/0.26	SHGC = 0.21/0.19

* Replacement; 270 Duraseal & Argon, ** 366 Duralite & Argon; Note: U-Factor, insulation value. SHGC, Solar Heat Gain Coefficient, Rev 4/2/25

AAMA (36 x 64")	Grade H-R 35
Design Pressure Rating	DP 35
Air Infiltration	0.08 CFM
Water Resistance	@ 5.25 PSI No leakage
Forced Entry	Passed