



Windowcrafters

2033 Tucker Industrial Road, Tucker, GA 770-723-9900 www.windowcrafters.inc

900 Series Single Hung Vinyl Windows

Material	Chelsea Rigid PVC Vinyl Extrusions
Color	Cream White or Tan
Operating Sashes	Bottom
Tilt-in Feature	Bottom
Frame Thickness	2 7/8"
Application	New Construction – NC or Replacement box unit - R
Styles	Single Hung, Twin, Triple, Combination Unit, 2 lite slider, 3 lite slider, picture window, deadlight, shapes
Construction	Fusion-welded vinyl frame and sashes for superior strength and durability and multi-chamber frame for enhances thermal insulation and structural performance. Brickmold look exterior frame detail, reinforced meeting rail and integrated lift handles. Optional: PVC sash reinforcement
Glass	Standard - Cardinal 270® LoE, Optional: Cardinal 366® LoE
Spacer	Dura Platform® warm edge spacers in a 3/4" dual pane insulated glass. Optional: Duralite, Optional: Argon gas fill
Grids	GBG and SDL - optional
Balance System	Inverted Balance System
Weather-stripping	Clear fin with dual-edge white nylon pile, Optional: upgrade
Sash Locks	Composite Integral Interlocks, double locks on units 28" or wider
Tilt Latch	Composite, right and left side on bottom sash
Bulb Seal	Seamless compression bulb seals nearly 100% closed cell for water penetration
Screen	Low profile 3/4" Aluminum Frame / nylon mesh - half height

Performance Metric	Cardinal 270LoE / Argon Gas / Duraseal	Cardinal 366LoE / Argon Gas, Duralite
U-Factor	0.29	0.27
SHGC	0.30	0.22
Air Infiltration	<.30 CFM	<.30 CFM
Design Pressure - 35	Water Resistance 5.25 PSI No Leak	Forced Entry - Passed

AAMA Certified